

Specifications



A.1 Physical Specifications

Table A-1 System Physical Specifications

	U.S.	Metric
Height	25.5 in	64.5 cm
Width	17 in	43.2 cm
Depth	23.5 in	59.7 cm
Weight	160 lb, approx	72.7 kg, approx
Power cord	6 ft	1.8 m

Table A-2 Clearance and Service Access

	U.S.	Metric
Front	18 in	45.7 cm
Rear	18 in	45.7 cm
Left	6 in	15 cm
Right	6 in	15 cm

Table A-3 Shipping Specifications

	U.S.	Metric
Height	34 in	86 cm
Width	29 in	74 cm
Depth	22.5 in	57 cm
Weight	185 lb, approx	84 kg, approx

A.2 Electrical Specifications

Table A-4 Server Electrical Specifications

Parameter		Value
Input current	Voltage range	100-120 Vac or 200-240 Vac
	Current, maximum	8.5A
	Current frequency range	47-63 Hz
Input power rating	Total continuous power	750W
Volt-Ampere rating		825 VA
BTU rating		2600 BTU
Power factor		0.92 - 0.96
Plug type	U.S.	NEMA 5-15P
	International	10A, single phase IEC 320, C14

A.3 Environmental Requirements

Table A-5 Temperature, Humidity, and Altitude Limits

	Operating	Nonoperating
Temperature	41 [°] F to 104 [°] F (5 [°] C to 40 [°] C*)	-4 [°] F to 140 [°] F (-20 [°] C to 60 [°] C)
Humidity	20% to 80% RH noncondensing, 27C max wb	93% RH
Altitude	9,843 ft (3 km)	39,370 ft (12 km)

***Maximum operating temperature is 95[°]F (35[°]C) when using tape media.**
